

DNA-120


ALL-BLACK DESIGN


330W | 325W | 320W





Maximize Energy Production

High-efficiency, Half-cut cell panel

 Advanced technology boosts power generation

 Designed & engineered for extreme weather
5400 Pa snow load
5400 Pa (210 mph) wind load

 All-black design for pristine aesthetics


 25 year extended product warranty*
30 year extended peak power warranty*

Our DNA Half-cut Cell Series impressively combines advanced technologies to maximize performance. Our patented DNA, Dual Nano Absorber, technology allows for panel operate at high efficiencies with excellent performance in high temperature environments.

*Aptos Solar Technology solar panels come with a standard 15 product warranty and 25 year peak power warranty. Customers must select optional warranty upgrade package to qualify extended 25 year product warranty and extended 30 year peak power warranty.

www.aptosolar.com | info@aptossolar.com

Linear Performance Warranty




Factory Certifications



Product Certifications





DNA-120

BLACK FRAME, BLACK BACK-
HIGH EFFICIENCY, HALF-CUT CELL PANEL



ELECTRICAL SPECIFICATIONS (+3%/-0%)

DNA-120-MF23-320W DNA-120-MF23-325W DNA-120-MF23-330W

STCrated output P_{mpp} (W)	320	325	330
Module Efficiency	18.96%	19.25%	19.54%
Open Circuit Voltage V_{oc} (V)	39.92	40.10	40.27
Short Circuit Current I_{sc} (A)	10.35	10.43	10.51
Rated Voltage V_{mmp} (V)	32.51	32.71	32.91
Rated Current I_{mmp} (A)	9.84	9.93	10.02

Standard Test Conditions for front-face of panel:
1000 W/m², 25 °C, measurement uncertainty ≤3%


TEMPERATURE COEFFICIENTS

Temperature Coefficients P_{mpp}	-0.40%/°C
Temperature Coefficients I_{sc}	+0.046%/°C
Temperature Coefficients V_{oc}	-0.306%/°C
Normal Operating Cell Temperature (NOCT)	45 °C


TEST OPERATING CONDITIONS

Maximum Series Fuse	20A
Maximum System Voltage	1,500 VDC (UL&IEC)
Maximum Load Capacity (Per UL1703)	Front Load: 5400 PA Snow load / 113 PSF / 2052 lbs. Rated Load Rear Load: 5400 PA Wind load / 113 PSF / 210 MPH Rated Load
Fire Performance Class	Class C/Type 1

MODULE DIMENSIONS



I-V CURVE



MECHANICAL PROPERTIES

Cell Type	Monocrystalline
Glass	Low Iron, Tempered
Frame	Anodized Aluminum Alloy
Junction Box	IP67
Dimension	1684 x 1002 x 35mm
Output Cable	4mm ² (EU)12AWG, 39.37in(1000mm)
Weight	41.9lbs.(19kg)
Cable Length	1200mm

PACKAGING CONFIGURATION

Number of Modules per Pallet	30
Number of Pallets per 40ft HQ Container	26
Pallet Dimensions (mm)	1720X 1140 X 1140
Pallet weight (kg)	620
Container weight (kg)	16120

PRODUCT CERTIFICATIONS

